



Husqvarna K 4000

This electric all-round cutter minimises the amount of water and slurry. Unlike other electric cutters, the blade rotates forward, cutting into the material efficiently with minimum effort on the operator. K 4000 is easily adaptable for dry cutting with the Vac attachment accessory for minimal dust generation.

Engine

Rated input power	2.4 hp
Voltage	100-120 V
Frequency	50-60 Hz

Dimensions

Product size length	24.8 in
Product size width	8.7 in
Product size height	12.3 in
Weight	16.8 lbs

Vibrations

Vibrations left/front handle	3.5 m/s ²
Vibrations right/rear handle	3.5 m/s ²

Cutting equipment

Cutting depth, max	5 in
Blade diameter, max	14 in
Arbor diameter	1 in
Blade thickness, max	0.22 in
Peripheral speed, max	19690 fpm

Hydraulics

Sound and noise

Sound power level, guaranteed (LWA)	105 dB(A)
Sound pressure level at operators ear	95 dB(A)

Certifications

Articles for K 4000

Husqvarna K 4000

967 08 40-01

Features for K 4000

Constant-flow water valve



The integrated regulator controls the water volume, ensuring a constant flow to the blade. It also ensures the amount of water is sufficient to bind the dust without creating an excess of water.

Ergonomically designed rear handle



Power cord inlet located underneath the handle enables ease of use and comfortable handling with hassle free operation.

Increased productivity



The new pop-up carbon brushes protects the collector from unforeseen rotor changes which increases reliability and enables longer service intervals.

Easy serviceability



The one-piece inspection lid and Torx screws make it easy to assemble and service.