



PCMS-1500C-S G3 MTO

TRAILER-MOUNTED MESSAGE SIGN

Ver-Mac's PCMS-1500C-S G3 MTO is our largest full-matrix trailer-mounted portable changeable message sign, and is approved for use in Ontario.

The PCMS-1500C-S G3 MTO features our pixel failure detection technology, NTCIP-compliant* V-Touch Controller and Stealth Technology.

This unit combines an energy-efficient design and high-quality construction to provide the most reliable and cost-effective message sign on the market. The PCMS-1500C-S G3 MTO is the only model approved for highway construction in Ontario.



STEALTH TECHNOLOGY

Sealed maintenance-free batteries Anti-theft hidden battery compartment

ROBUST TRAILER DESIGN

Tongue wheel jack for safe and easy set up Controller located away from the road Rugged indexed rod mast brake

ENERGY-EFFICIENT DESIGN

HIGH-CONTRAST ELECTRONIC CARDS

Create bold and bright characters with greater angularity

3 X 85W TILT-AND-ROTATE SOLAR PANELS

Panels tilt to a 45° angle to provide maximum solar recharging during all four seasons

10 X 12-VOLT DEEP-CYCLE BATTERIES

Designed to run 12 months in most regions without manual recharging



APPLICATIONS

- Highway construction
- Ministry of Transportation (MTO)
- Smart work zones
- Special events



HIGH-QUALITY CONSTRUCTION

SUPERIOR POWDER COATING FINISH

Impact, humidity, salt spray and rust resistant

4 LEVELING JACKS WITH OUTRIGGERS

For stabilization and easy transportation

ELECTRO-HYDRAULIC LIFT MECHANISM

For quick and effortless deployment

3-IN. (76 MM) PINTLE EYE HITCH



V-TOUCH CONTROLLER

NTCIP* COMPLIANT

EASY-TO-READ

7-inch (178 mm) color LCD touchscreen display

USER-FRIENDLY

One-click icon-based menu items

TIME-SAVING

Create your own library of messages

SIMPLE TO OPERATE

Intuitive point-and-go icons make displaying and editing messages quick and easy

ADDITIONAL FUNCTIONALITIES

Scheduling, sign diagnostics, pin-protected security, and much more



DISPLAY

- Display panel:
 83 x 145 in. (2100 x 3694 mm)
- Pixel failure detection technology
- Full-matrix of 30 x 56 pixels
- 4 LEDs per pixel
- Up to 3 lines of 12 characters per line
- Display sign rotates 360° for perfect setting
- Plug-and-play display modules for simplified maintenance

DIMENSIONS AND WEIGHT

- Overall length: 183 in. (4650 mm)
- Overall width: 87 in. (2203 mm)
- Traveling height: 114 in. (2895 mm)
- Operating height: 207 in. (5258 mm)
- Axle/suspension: 3,500 lb (1587 kg)
- Weight (approx.): 2,300 lb (998 kg)

OPTIONS

- Radar
- Data logger
- PTZ camera

Other options are available to meet your needs.

WARRANTY

- 1-year warranty on complete trailer
- 2-year warranty on electronic components manufactured by Ver-Mac





