

# Husqvarna PG 400

## Applications

- Capable of grinding adhesive residue, paint and epoxy on large concrete areas.
- Efficient removal of carpet glue, mastic, roofing tar, etc.

## Benefits

- The self-adjusting floating cover with brush list follows the surface and creates a tight seal to prevent dust from entering the surrounding environment.
- The chassis/frame can be separated from the grinding head in less than 30 seconds. The frame folds tightly and can be wheeled around. Having two separate pieces enables the grinder to fit into the trunk of most vehicles.
- The speed is fixed and no settings are required.
- Powerful 6.5 hp, 3-phase motor enables high production rates.

**CSA Approved**

230-240V model


*\*1-phase units come with 50' 10 gauge extension cord*

	PG 400 380-480 V	PG 400 230-240 V	PG 400 230-240 V
Item No.	967966405	967648504	967966406

## Technical Specifications

Power, hp (kW)	6.5 (4.8)	6.5 (4.8)	4 (3)
Voltage, V	480	220 - 240	220 - 240
Plug Type	L16-20	L15-20	L6-30
Rated current, amps	9	15	18
UL & CSA approved	-	Yes	Yes
Power supply	3-Phase	3-Phase	1-Phase
Grinding width, in (mm)	16 (400)	16 (400)	16 (400)
Grinding disc, in (mm)	16 (400)	16 (400)	16 (400)
Grinding disc segment capacity	18	18	18
Grinding pressure total, lbs (kg)	143 (64)	143 (64)	143 (64)
Grinding disc speed, rpm	1,720	1,720	1,720
Direction of rotation (viewing from operator's position)	Clockwise	Clockwise	Clockwise
Dimensions (L x W x H), in (mm)	55 X 20 X 41 (1,400 X 510 X 1,050)		
Dust port size, in (mm)	2 (51)	2 (51)	2 (51)
Weight, lbs (kg)	254 (115)	254 (115)	254 (115)
Recommended generator size, kW	12	12	12
Recommended dust extractor size, CFM	350+	350+	350+