

SERIES 2100 CONTRACTOR LIFT

A Versatile, Inexpensive Contractor Lift

Series 2100 Features:

- Lifts 650 lb (300 kg)
- 12, 18 and 24 foot heights (3.9, 5.6 and 7.2 m)
- Lightweight
- All the features of the Series 2000 lift at a lower price!

Pulley Guards

Load cable cannot come off.



Reversible Forks

Using plunger pins, forks remove and reverse easily for added height or to get flush with a ceiling. No loose pieces!

Loading Bar

Great for overhead cranes

Roller Wheels

Helps to roll into trucks or vans

Inside-Mast Cable Feed

Cable feeds inside mast, removing exposed cable from near the operator's face.

Sumner-built Winch

Highly reliable, single-speed winch uses idler roller to feed cable evenly on the drum to avoid cable flats. Handles are removable when not in use.



10" Rough Terrain Wheels

Makes loading a truck or van hassle free.

Lockable 5" Casters

Hard tread urethane wheels with Delrin® bearings.

Fast Action Stabilizer Legs

Mounted on base top, stabilizer legs fold down with ease and lock in place. Optional on model 2112.

Part #	Description	Max Height		Lifting Capacity		Lift Weight		Shipping Weight	
		Feet	Meter	lbs	kg	lbs	kg	lbs	kg
783650	2112 Contractor Lift	12' 11-3/8"	3.9	650	300.0	252	114.5	287	130.5
783651	2118 Contractor Lift	18' 4-3/8"	5.6	650	300.0	321	145.9	356	161.8
783652	2124 Contractor Lift	23' 9-3/8"	7.2	650	300.0	366	166.0	399	181.4

Available in
Optional
Galvanized
Finish!
Part # 776270



One piece slide-lock mechanism releases with plunger pins to fold legs. Leg rollers allow lift to be wheeled around with legs in stored position.

Optional Features for Sumner* 2100 Lifts



Boom Carriage (Part # 783642)

Ideal for installing pipe or lifting "from the top" applications. Uses four attaching plunger pins and has a 40" (100 cm) reach. Hook has five locations with load capacities of:
650 lbs (300 kg), 525 lbs (240 kg)
425 lbs (195 kg), 300 lbs (135 kg)
200 lbs (90 kg)



Pipe Cradle (Part # 783705)

Great for duct pipe or other HVAC applications. Slides over standard forks. Packaged in sets of two.



Steering Handle (Part # 786695)

Optional steering handle improves maneuverability of lift. With a push of a release button, handle folds out of the operator's way.



Fork Extensions (Part # 783691)

With the push of a button, forks may be extended from 28" to 42" (71-106 cm). With longer forks, the weight capacity decreases to 200 lbs (90 kg) and is clearly displayed on the forks when extended. A second button returns the extension for convenient storage inside the forks.



Two Speed Winch Handle Kit (Factory Installed Part # 783765)

The two speed winch handle offers a standard speed setting or a high speed setting for quickly positioning forks in half the time. Available only on Series 2100 lifts commencing with serial number 9433. For field installation kit, use part #783761.

Safety Brake

Each mast and carriage can have a factory installed, gravity actuated safety brake which holds loads in place to help avoid any slack in the cable.

Part #	Description
783882	Safety brake - 2112
783883	Safety brake - 2118
783884	Safety brake - 2124

Series 2100 Contractor Lift Dimensions	2112		2118		2124	
Height - stowed	84"	2.13 m	84"	2.13 m	84"	2.13 m
Length - stowed	34"	0.86 m	34"	0.86 m	34"	0.86 m
Height - operating	84"	2.13 m	84"	2.13 m	84"	2.13 m
Length - operating	62"	1.57 m	73"	1.84 m	73"	1.84 m
Base width	31-1/4"	0.80 m	31-1/4"	0.80 m	31-1/4"	0.80 m
Width with stabilizer legs	74"	1.88 m	74"	1.88 m	74"	1.88 m
Ground clearance	2-1/2"	6.4 cm	2-1/2"	6.4 cm	2-1/2"	6.4 cm
Load height (minimum)	6"	15.2 cm	6"	15.2 cm	6"	15.2 cm
Maximum height (forks down)	10' 11-5/8"	3.3 m	16' 4-5/8"	5.0 m	21' 9-5/8"	6.6 m
Maximum height (forks reversed)	12' 11-3/8"	3.9 m	18' 4-3/8"	5.6 m	23' 9-3/8"	7.2 m