

SPECIFICATIONS

PART #	NET WEIGHT	NET SHIPPING WEIGHT	DIMENSIONAL WEIGHT	INSIDE DIAMETER OF BASE	OVERALL LENGTH	OUTSIDE DIAMETER OF BASE	DIAMETER OF TOP OF HORN	AIR INLET (NPT)	BOLT CIRCLE DIAMETER	BASE SLOT DIAMETER
TX3AMS	6.4 lbs. 2.9 kg	7.0 lbs. 3.2 kg	7.0 lbs. 3.2 kg	3" 8 cm	16.5" 42 cm	7.25" 18 cm	6.0" 15 cm	1/2" 13 mm	6.75" 17 cm	.38" 10 mm
TX3AMS-P	4.7 lbs. 2.1 kg	6 lbs. 2.7 kg	6 lbs. 2.7 kg							
TX3AMS-SH	5.8 lbs. 2.6 kg	7 lbs. 3.2 kg	7 lbs. 3.2 kg							
TX3AM	9.6 lbs. 4.4 kg	11 lbs. 4.9 kg	10.8 lbs. 4.9 kg	3" 8 cm	32.0" 81 cm	7.25" 18 cm	7.0" 18 cm	1/2" 13 mm	6.75" 17 cm	.38" 10 mm
TX3AM-P	6.3 lbs. 2.9 kg	8 lbs. 3.6 kg	10.8 lbs. 4.9 kg							
TX3AM-SH	8.15 lbs. 3.7 kg	10 lbs. 4.5 kg	10.8 lbs. 4.9 kg							
TX6AM	24.45 lbs. 11.1 kg	29 lbs. 13.2 kg	40.0 lbs. 18.1 kg	6" 15 cm	44.0" 112 cm	11.18" 28 cm	12.5" 32 cm	1" 25 mm	10.5" 27 cm	.44" 11 mm
TX6AM-P	16.35 lbs. 7.5 kg	21 lbs. 9.5 kg	40.0 lbs. 18.1 kg							
TX6AM-SH	20.85 lbs. 9.5 kg	25 lbs. 11.3 kg	40.0 lbs. 18.1 kg							
TX6AM-SS	37.5 lbs. 17.0 kg	42 lbs. 19.1 kg	40.0 lbs. 18.1 kg							
TX8AM	36.25 lbs. 16.4 kg	42.0 lbs. 19.1 kg	62.0 lbs. 28.1 kg	8" 20 cm	46.44" 118 cm	14.25" 36 cm	14.31" 36 cm	1" 25 mm	13.5" 34 cm	0.5" 13 mm
TX8AM-P	25.65 lbs. 11.6 kg	31 lbs. 14.1 kg	62.0 lbs. 28.1 kg							
TX8AM-SH	32.4 lbs. 14.7 kg	38 lbs. 17.2 kg	62.0 lbs. 28.1 kg							
TX10AM	42.5 lbs. 19.3 kg	49 lbs. 22.2 kg	93.0 lbs. 42.2 kg	10" 25 cm	48.0" 122 cm	16.75" 43 cm	15.75" 40 cm	1" 25 mm	15.5" 39 cm	1" 25 mm
TX10AM-P	31.1 lbs. 14.1 kg	38 lbs. 17.2 kg	93.0 lbs. 42.2 kg							
TX10AM-SH	38.75 lbs. 17.6 kg	46 lbs. 20.9 kg	93.0 lbs. 42.2 kg							

PERFORMANCE

PART #	COMPRESSED AIR PRESSURE (PSI) / (BAR)	AIR FLOW (Free Flow) CFM / M3/Hr	COMPRESSED AIR CONSUMPTION CFM / M3/Hr	DECIBEL LEVELS (5 FEET)
TX3AMS	40 / 2.75	815 / 1384	21 / 35	64
TX3AMS-P	60 / 4.14	863 / 1466	31 / 52	66
TX3AMS-SH	80 / 5.52	1076 / 1828	41 / 69	68
	100 / 6.89	1205 / 2047	51 / 86	71
TX3AM	40 / 2.75	1017 / 1727	21 / 35	64
TX3AM-P	60 / 4.14	1135 / 1928	31 / 52	69
TX3AM-SH	80 / 5.52	1308 / 2222	41 / 69	72
	100 / 6.89	1465 / 2489	51 / 86	73
TX6AM	40 / 2.75	2385 / 4052	43 / 73	68
TX6AM-P	60 / 4.14	2560 / 4349	60 / 101	73
TX6AM-SH	80 / 5.52	3020 / 5131	81 / 137	75
TX6AM-SS	100 / 6.89	3698 / 6282	101 / 171	78
TX8AM	40 / 2.75	3152 / 5355	78 / 132	72
TX8AM-P	60 / 4.14	4215 / 7161	108 / 183	77
TX8AM-SH	80 / 5.52	4810 / 8172	142 / 241	79
	100 / 6.89	5435 / 9234	178 / 302	81
TX10AM	40 / 2.75	4898 / 8321	134 / 227	76
TX10AM-P	60 / 4.14	6182 / 10503	189 / 321	81
TX10AM-SH	80 / 5.52	7304 / 12409	252 / 428	83
	100 / 6.89	8220 / 13965	380 / 645	85