



## Product Description

Industrial VAF3000A/B – On-demand performance. Ideal for use in confined spaces that require a powerhouse air ventilator, the VAF3000A/B can handle your most demanding industrial needs. With a forceful 1 hp motor, the VAF3000 can deliver both positive and negative airflow at an incredible maximum capacity of 2,796 CFM in the most difficult work environments.

## Features

Industry leading airflow in all sizes, rated from 750-10,000 cfm

Dual wall polyethylene housing designed to withstand the harshest of conditions, providing years of durability and dependability

Premium quality motors rated for over 100,000 hours of heavy duty, continuous use for unmatched return on investment

Safety tested to UL, CSA and CE certifications, exceeding industry standards

Provides positive and negative airflow (blows and extracts)

Lightweight for easy portability

Stackable to save storage space

Three year warranty

Made in the USA

## Specifications

<b>Blade Color</b>	Black
<b>Brand</b>	Schaefer
<b>Cfm (free Air)</b>	2796
<b>Cfm (with 25' Of Duct)</b>	1830
<b>Drive</b>	Direct
<b>Housing Material</b>	Polyethylene
<b>Maximum Duct Length (feet)</b>	125
<b>Phase</b>	1
<b>Speeds</b>	1
<b>Cfm/watt (free Air)</b>	3.6
<b>Cord</b>	Included - Wired
<b>Diameter (inches)</b>	12

<b>Nameplate Amps</b>	9.0/9.0
<b>Number Of Wings</b>	7
<b>Power (hp)</b>	1
<b>Product Dimensions (L X W X H Inches)</b>	21" x 17" x 14"
<b>Product Net Weight (lbs)</b>	32.5
<b>Performance Test #</b>	498
<b>Switch</b>	On product
<b>Voltage</b>	115
<b>Maximum Rpm</b>	3300
<b>Blade Material</b>	Polypropylene
<b>Cfm Calculation Standard</b>	ANSI/AMCA Standard 230-99

<b>Able To Ship Small Parcel</b>	Yes
<b>Cfm Range (free Air)</b>	2501 - 5000
<b>Cord Length (feet)</b>	20
<b>Distinguishing Feature</b>	Suitable with Ducting
<b>Fixed Or Portable</b>	Portable
<b>Guard Material</b>	Powder Coated Steel
<b>Oscillating</b>	No
<b>Product Certifications</b>	cULus
<b>Country Of Origin</b>	US
<b>Guard Spacing (inches)</b>	1/2 OSHA

Frequency (hz)	60/50
Guard Color	Black



Pallet Quantity	20
Product Color	Blue
Product Shipping Dimensions (in)	18 x 16 x 24

Housing Color	Blue
Maximum Static Pressure (in. H2o)	3